

AMGR-90

DIESEL GENERATOR





GROUP		Standby Power	Prime Power	
Power	kVA	90	81,8	
Power	kW	72	65,4	
Engine Speed	rpm	1500		
Standard Voltage	V	400 / 230		
Power Factor	Cos Phi	0,8		

Continuous Power

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a constant electrical load. Average load can be 100%. The generator must not be overloaded.

Standby Power

The maxpower available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utilitypower outage or under test conditions for up to 200 hrs of operation per year under average of 70%load.Overloading isn't permissible.

Prime Power

The maximum power which a generating set is capable of delivering continuouslywhilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

Niyazi Mahallesi Leblebici Sokak No: 17/A Battalgazi / Malatya

www.amgpower.com.tr



+90 422 322 16 84 | info@amgpower.com.tr

AMG POWER

AMGR-90


Alternator Properties


Engine Properties

Brand		RICARDO
Model		R4105IZLD
Standby	kW	96,8
Prime	kW	88
Cylinder Displacement	lt.	4,6
Number of Cylinders / Type		4 / In line
Bore x Stroke	mmxmm	105x135
Compression Ratio		17:1
Governor Type		Mechanic/Electronic
Idle Speed	rpm	1500
Aspiration		Turbocharge, Intercooler
Injection Type		Direct Injection
Cooling System		Liquid Cooled
Fuel Consumption%100	lt/h	23,4
Fuel Consumption%75	lt/h	17,5
Fuel Consumption%50	lt/h	11,7
Oil Capacity	lt.	13
Cooling Liquid Capacity	lt.	22
Voltage	V	24
Battery Capacity	А	2x60

· · ·			
Output Voltage	V	230/400	
Frequency	HZ	50	
Automatic Voltage Regulation	±%	0,5	
Phase		3	
Pole		4	
Overload		1 Hour %110	
Voltage Regulation		±%1	
Power Factor	Cosq	0,8	
Warning System		Self Alert	
AVR Model		SX460	
Total Harmonic Losing		≤%3	
Connecting Type		Star	
Protection Class	IP 23		
Isolation Class	Н		

Diemensions





Canopied

L x W x H	mm	2650x950x1660	L x W x H	mm	2350x950x1400
Weight	kg	1363	Weight	kg	1088
Fuel Tank Capacity	lt.	160	Fuel Tank Capacity	lt.	160

Standard Specification

Some standard equipments that AMG POWER provides with generator

- sets; •50°C cooland radiator
 - Flexible fuelpipes and oil drain valve
 - Engine jacket heater
 - 4 pole synchronous type self-excited brushless alternator
 - Battery and wires
 - Entegrated fuel tank

- User and maintenance manual
- Oil and antifreeze
- Datakom D-300 controller
- Battery charger
- Electrical circuit diagram

Niyazi Mahallesi Leblebici Sokak No: 17/A Battalgazi / Malatya

www.amgpower.com.tr



+90 422 322 16 84 | info@amgpower.com.tr



AMGR-90



- Diesel and gas genset support
- 400Hz operation support
- Downloadable languages
- Harmonic analysis of V & I
- Weekly operation schedule
- Dual mutual standby with equal aging of gensets
- Overload IDMT protection
- Current unbalance protection
- Fuel filling & fuel theft alarms
- Battery back-up real time clock

- Idle speed control
- Contactor & MCB drive
- · Fuel filling counters
- Fuel consumption counter
- Automatic GSM geo-location
- Reverse power protection
- Free configuration program
- Mobile genset support
- 3 level configuration password
- Ip65 rating with optional gasket

Optional Specification

Some Optional Equipments that AMG POWER provides with generator Sets;

- Auto refueling system
- Extra fuel tank , coil heaters
- Remote radiator
- Syncronization system
- Circuit breaker

- Special soundproof canopies
- Siesmic solutions
- Trailer
- Remote control panel
- Automatic transfer switch

www.amgpower.com.tr

